## [PP-10]

## Numerical simulation of the reflex triode virtual cathode with an intense relativistic electron beam

Wook Jeon, Kew Yong Sung, Jin Gi Kim, Yoon Seo, and Eun Ha Choi
Charged Particle Beam and Plasma Laboratory,
Department of Electrophysics / Pulse Driven Power Research Center Kwangwoon University,
447-1 Wolgye-Dong, Nowon-Gu, Seoul 139-01, Korea

A virtual cathode reflex triode is investigated by numerical simulation with a 3-dimensional particle-in-cell (PIC) code called MAGIC. The reflex triode virtual cathode oscillator has a disk cathode and a disk anode-mesh. Here anode-cathode (A-K) gap distance has been varied from 10mm to 30mm. Simulation results show that the output microwave frequency has a narrow bandwidth and its output microwave power depends sensitively A-K gap distance. Output microwave mode is mixture of TE mode at A-K gap distance 10mm, however, TE is to be dominant mode at A-K gap distance 30mm

## [References]

- [1] R.B. miller, An introduction to the Physics of intense charged particle beam. New York: Plenum, 1982, chaps. 2,3,5.
- [2] E. H. Choi, M. C. Choi, Y. Jung, M. W. Chong, J. J. Ko, Y. Seo, G. S. Cho, H. S. Uhm, H. Suk, "High-power microwave generation from an axially extracted virtual cathode oscillator", IEEE Trans. Plasma Sci., vol. 28 (no. 6), pp. 2128-2134 (2000)
- [3] A.L.Peratt, C. M. Snell, and Thode 'High power reflex triode microwave source", IEEE Transactions on Plasma sci, vol.ps-13 No.6 December 1985.