

High cell density culture of *Anabaean variabilis* using repeated additions of nutrients and light energy

Jong Hyun Yoon¹, Jong-Hwan Shin¹, Eun Kyoung Ahn¹,
Sang Jun Sim², Mi-Sun Kim³, Tai Hyun Park^{1,*}

¹School of Chemical and Biological Engineering, Seoul National University, Seoul

²Department of Chemical Engineering, Sungkyunkwan University, Suwon

³Biomass Research Team, Korea Institute of Energy Research, Daejeon

TEL: +82-2-880-8020, FAX: +82-2-875-9348

Abstract

The basic requirements for high-density photoautotrophic cyanobacterial cultures in photobioreactors are suitable medium composition and proper light energy. Because phosphate was consumed first among nutrients in BG 11 medium, initial phosphate concentration in the medium was increased from 15 to 60 mg/l. Cell concentration reached 3.8 g dry cell/l in 6 days when initial phosphate concentration was 45 mg/l. As the increase of light lengthened the period of exponential growth phase and medium addition increased final cell density, high cell density culture was achieved using repeated additions of both nutrients and light energy. The final concentration was 4.6 g dry cell/l in 4.5 days.

References

1. Yoon J. H., et al., High cell density culture of *Anabaena variabilis* using repeated injections of carbon dioxide for the production of hydrogen (2002), *Int. J. Hydrogen Energy*, **27**(11-12), 1265-1270.
2. Cogne G., et al., Uptake of macrominerals and trace elements by the cyanobacterium *Spirulina platensis* (*Arthrospira platensis* PCC 8005) under photoautotrophic conditions: culture medium optimization (2003), *Biotechnol. Bioeng.*, **81**(5), 588-593.
3. Mandalam R. K., et al., Elemental balancing of biomass and medium composition enhances growth capacity in high-density *Chlorella vulgaris* Cultures (1998), *Biotechnol. Bioeng.*, **59**(5), 605-611.
4. Choi S-L, et al., Lumostatic operation of bubble column photobioreactors for *Haematococcus pluvialis* cultures using a specific light uptake rate as a control parameter (2003), *Enzyme Micro. Technol.*, **33**(4), 403-409.