

Excellent Magneto-transport Properties of $\text{La}_{0.7}\text{Sr}_{0.3}\text{Mn}_{1+d}\text{O}_3$ -manganese Oxide Composite Films on YSZ Substrates Prepared by Aerosol Deposition

Hyo-Jin Kim, Young-Joon Yoon¹, Sung-Hwan Cho¹ and Sang-Im Yoo*

Department of Materials Science and Engineering, Research Institute of Advanced Materials (RIAM),
Seoul National University, Seoul 151-744, Korea

¹Korea Institute of Ceramic Engineering and Technology (KICET), 233-5 Gasan-Dong,
Geumcheon-Gu, Seoul 153-801, Korea

*e-mail : siyoo@snu.ac.kr

We report excellent magneto-transport properties of pure $\text{La}_{0.7}\text{Sr}_{0.3}\text{MnO}_3$ (LSMO) and LSMO-manganese oxide composite films which were prepared on YSZ (yttria stabilized zirconia) substrates by aerosol deposition and then followed by the post-annealing at high temperatures of 1000~1200°C for 2 h in air. While as-deposited films commonly show poor magnetic properties, the post-annealed films exhibit very good magnetic properties with Curie temperatures ranging from 355 to 370 K. Remarkably improved LFMR properties and dMR/dH values are observed in all LSMO-manganese oxide composite films compared with pure LSMO films, suggesting that a magnetic disorder at the LSMO grain boundary, known as a key factor suppressing effective spin-dependent scattering, can be greatly improved by the manganese oxide phase. The largest LFMR value of 1.2% at 300 K and 0.5 kOe was obtained from LSMO-manganese oxide composite films annealed at 1200°C. Details will be presented for a discussion. This work was supported by the National Research Foundation of Korea (NRF) grant funded by the Korea government (MEST) (No.2011-0002897).